

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Assistant Commissioner for Patents
United States Patent and Trademark
Office
Box PCT
Washington, D.C.20231
ETATS-UNIS D'AMERIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 24 May 2000 (24.05.00)	
International application No. PCT/GB99/03439	Applicant's or agent's file reference DCM/GW/CB/P10099PC
International filing date (day/month/year) 18 October 1999 (18.10.99)	Priority date (day/month/year) 21 October 1998 (21.10.98)
Applicant BECKERS, Stefan, D. et al	

1. The designated Office is hereby notified of its election made:



in the demand filed with the International Preliminary Examining Authority on:

11 May 2000 (11.05.00)



in a notice effecting later election filed with the International Bureau on:

2. The election ☒ was

was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Facsimile No.: (41-22) 740.14.35	Authorized officer Juan Cruz Telephone No.: (41-22) 338.83.38
--	---

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B29C 47/00, 47/10, 55/28, B01D 71/10, C08B 1/00, C08J 5/18		A2	(11) International Publication Number: WO 00/23249
(21) International Application Number: PCT/GB99/03439		(43) International Publication Date: 27 April 2000 (27.04.00)	
(22) International Filing Date: 18 October 1999 (18.10.99)		(74) Agents: MCCALLUM, William, Potter & al.; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).	
(30) Priority Data: 9823080.8 21 October 1998 (21.10.98) GB 9823081.6 21 October 1998 (21.10.98) GB 9823083.2 21 October 1998 (21.10.98) GB 9823085.7 21 October 1998 (21.10.98) GB		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(71) Applicants (for all designated States except US): DEVRO PLC [GB/GB]; Moddiesburn, Chryston, Glasgow G69 0JE (GB). FRAUNHOFER-GESELLSCHAFT ZUR FORDERUNG DER ANGEWANDTEN FORSCHUNG E.V. [DE/DE]; Leonrodstrasse 54, D-80636 Munich (DE).		Published Without international search report and to be republished upon receipt of that report.	
(72) Inventors; and (75) Inventors/Applicants (for US only): BECKERS, Stefan, D. [BE/BE]; Panovenstraat 19, B-3941 Hechtel-Eskel (BE). WEIGEL, Peter [DE/DE]; Seelenbinder 3B, D-14532 Kleinmachnow (DE). FINK, Hans-Peter [DE/DE]; Kiefernweg 7, D-74513 Teltow (DE). DOSZ, Michael [DE/DE]; Hildburghauser Strasse 191A, D-12209 Berlin (DE). PURZ, Hans-Joachim [DE/DE]; Mairfelder Anger 30, D-14513 Teltow (DE).			

(54) Title: CELLULOSE EXTRUSION

(57) Abstract

A process and apparatus used in cellulose extrusion is disclosed. In particular, the process discloses using an inert gas blanket above a cellulose solution wherein the inert gas blanket reduces any undesirable colour variations in the extruded product. Furthermore, the apparatus discloses draw means positioned downstream of the extrusion means to continuously draw the extruded cellulose film from the extrusion means. Apparatus is also disclosed wherein a tubular member is used to receive an extruded blown tube. The product formed using the process and apparatus described herein which has a substantially uniform distribution of fine pores throughout its cross-section is also discussed.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

09/830044

JC02 Rec'd PCT/PTO 20 APR 2001

13/PRTS

WO 00/23249

PCT/GB99/03439

1

CELLULOSE EXTRUSION

This invention relates to a process and apparatus used in cellulose extrusion and the obtained product, i.e. extruded cellulose film in, for example, sheet or tubular form.

The process relates to extruding a solution of cellulose, water and an amine oxide according to the well-known amine oxide extrusion process. In particular, the process relates to the reduction or avoidance of degradation or discolouration of the extruded cellulose solution, which otherwise leads to poor product quality.

The apparatus also relates to the avoidance of variations in thickness and edge wrinkling of the extruded film.

The apparatus is also suitable for use in extrusion of a blown film into a precipitation medium.

The invention also relates to an extruded cellulose product having a novel structure.

The production of extruded cellulose articles, such as fibres, sheets or tubes has been known for more than a century. In this so-called "viscose" process, cellulose is derivatised with carbon disulphide and solubilised in diluted sodium hydroxide to form a solution and the solution is extruded. The extruded cellulose is then regenerated and reverts to its solid form. The viscose process has been used for the manufacture of sausage casings, flat cellophane films, rayon fibres, bottle caps etc. A disadvantage of the viscose process is that it employs carbon disulphide as an intermediate, which is environmentally undesirable.

More recently, the so-called "amine-oxide" process has been developed wherein the cellulose is dissolved in a mixture of water and an amine-oxide solvent. A commonly used amine-oxide solvent is the tertiary amine-oxide NMMO (N-methyl morpholine N-oxide). This solvent is able to dissolve cellulose without having to first derivatise the

WO 00/23249

PCT/GB99/03439

2

cellulose, as for example in the viscose process. Once solubilised the cellulose will precipitate from the solution as a regenerated cellulose product by contacting the solution with a precipitation liquid which is a non-solvent for cellulose and a solvent for NMMO. The most frequently used precipitation liquid for the amine-oxide process is water. Prior to extrusion, the cellulose amine-oxide solution may be heated to a temperature of around 100°C. Thermal stabilisers, such as propylgalate, may be added to the solution to inhibit the thermal degradation of NMMO.

It has now been surprisingly found that using the amine-oxide process, extruded cellulose films having novel structure and enhanced mechanical properties may be obtained.

Furthermore, it has been found when extruding cellulose films, that the extruded material was coloured brown-red. Moreover, the colour intensity varied between different extrusion runs in an apparently uncontrolled manner. Colour variation could even be observed during a single long extrusion run.

In the extrusion step of the amine-oxide process when used to produce tubular casings (for use, for example in the food industry), the tube is extruded into a bath of precipitation liquid. The precipitation liquid is also maintained within the extruded tube so as to solidify the cellulose from the inside. A slight positive pressure of air may be maintained above the precipitation liquid within the extruded tube so as to expand the tube in the transverse direction (ie. transverse to the machine extrusion direction). The presence of precipitation liquid within the extruded cellulose tube causes process difficulties after the tube emerges from the precipitation bath, since it is necessary to cut the tube at regular intervals in order to allow the liquid to drain away. Failure to do so, leads to undesirable stretching of the tube and variations in diameter and thickness.

WO 00/23249

PCT/GB99/03439

3

It is an object of the present invention to mitigate these problems.

According to a first aspect of the present invention there is provided a process for extruding a solution of cellulose, water and an amine-oxide, which comprises

- providing a closed vessel containing said cellulose solution;
- providing an inert gas blanket above the cellulose solution in the vessel; and
- delivering the cellulose solution to an extrusion means for extrusion thereof.

Thus, it has been surprisingly found that protecting the stored cellulose solution from oxidation by the provision of an inert gas blanket substantially mitigates against undesirable colour variations in the extruded product. Generally, the inert gas is nitrogen but other inert gases capable of protecting against oxidation might also be used.

The cellulose solution for extrusion comprises water and an amine-oxide. Suitable amine-oxides are known in the art and are particularly tertiary amine-oxides, such as NMMO (N-methyl morpholine N-oxide). Generally, cellulose pulp is mixed with an aqueous amine-oxide solution containing about 50% NMMO. The cellulose is unable to dissolve at such high water content. The water is then removed from the mixture by applying heat and reduced pressure. Typically, the pressure is set so the water boils off at approximately 70°C and the vapours are removed and recovered by re-condensation. Once the water content has been reduced from about 50% to about 12%, the NMMO mono hydrate is formed and the cellulose dissolves therein. The temperature is then typically increased to around 95°C to completely dissolve all the cellulose fibres. The reduced pressure is maintained or increased in order to remove any remaining air bubbles from the cellulose solution. This solution is then suitable for extrusion.

The solution may be extruded directly or stored for

WO 00/23249

PCT/GB99/03439

4

prolonged periods without detrimental effects. Furthermore, the solution may be solidified by decreasing the temperature (from around 100°C) to allow the solution to solidify and then ground to form pellets.

5 The cellulose solution ready for extrusion is stored in the closed vessel, which enables a blanket of inert gas to be maintained in the free space above the cellulose solution. The inert gas may be slightly pressurised in order to reduce ingress of air from outside the vessel, which might lead to deterioration of the stored cellulose solution. The use of a positive pressure of inert gas may also be of assistance in delivering the cellulose solution to the extrusion means.

10 The cellulose solution is extruded via the extrusion means into any desired shape, such as flat sheets or tubes. The process is particularly applicable to the production of wrappings or tubular casings for sausages, salami or other cased food products. The cellulose casing may be either used during the production of the food product and removed thereafter or may be retained in place.

15 According to a second aspect of the present invention there is provided an apparatus for the production of extruded cellulose film, which comprises

- 20 - extrusion means for continuously extruding a cellulose solution to form a cellulose film;
- 25 - precipitation means for solidifying the extruded cellulose film; and
- 30 - draw means positioned downstream of the extrusion means for continuously drawing the extruded cellulose film from the extrusion means.

35 Thus, it has surprisingly been found that providing a positive transport mechanism in the form of draw means to continuously draw the extruded film away from the extrusion means gives good control over the thickness of the extruded film.

 The cellulose solution for extrusion may be a viscose solution or an amine-oxide solution, according to known

WO 00/23249

PCT/GB99/03439

5

technology.

5 The extrusion means generally comprise an extrusion die shaped to extrude a cellulose film of desired shape and dimensions. In particular, the film may be in the form of a flat sheet or may alternatively be in the form of a tube. Flat cellulose sheets are used in the food industry for wrapping food products. Cellulose tubes are used to encase food products, such as sausages, salami or other cased food products. As mentioned above, particular problems arise with the production of tubular cellulose products, since it is necessary to maintain a volume of precipitation liquid within the tube to assist solidification thereof.

10 According to a preferred feature of the second aspect of the present invention, when the extruded cellulose film is tubular the draw means in the form of a pair nip rollers which draw the flattened tube away from the extrusion means. Preferably, the nip rolls act to hold the sides of the tube together to form a seal to retain the precipitation liquid in a fixed volume defined between the extrusion means and the draw means. This avoids carry over of liquid downstream and thus minimizes the need to cut the extruded cellulose tube at regular intervals to release carried over liquid. This represents a saving in materials and also in labour costs.

20 In order to facilitate flattening of the tube prior to the draw means (eg. the nip rollers) it is preferred to provide collapsing means for collapsing the tube from its tubular form towards a flattened form. The collapsing means may be in the form of opposed non-parallel guide plates having a decreasing spacing towards the draw means, typically at an angle of 10 to 35°, preferably 15 to 25°.

30 In a particular embodiment, the draw means and the collapsing means are combined into a single unit in the form of a pair of opposed non-parallel moving belts which are spaced at an end where the extruded tube enters and come closer progressively towards a nip at the draw means. The moving belts have the benefit of positively

WO 00/23249

PCT/GB99/03439

6

transporting the extruded tube through the collapsing means and into the draw means.

Where the collapsing means are stationary, they will generally be coated with a low friction material, such as PVDF. Where the collapsing means are in the form of a moving belt, a belt such as a rubber belt having a suitable surface roughness for transporting the cellulose tube will be chosen.

It is found that the presence of the collapsing means helps to avoid wrinkling of the edges of the flattened tube.

The precipitation means generally comprises a liquid. The liquid may be present in a bath or may be showered onto the extruded film. In the case of the amine-oxide process, the precipitation liquid is generally water or dilute aqueous amine-oxide solution.

The draw means is generally in the form of a pair of nip rollers having a surface formed of a material having appropriate frictional qualities for gently gripping the extruded film without damaging it. The draw means may be driven at a speed which is slightly faster (for example 10 to 250% faster) than the speed of the extrusion means in order to expand the extruded cellulose film in the longitudinal machine direction.

The present invention also relates to a corresponding process for the production of extruded cellulose film.

The present invention when applied to the production of extruded cellulose tube allows the maintenance of a fixed internal volume of precipitation liquid downstream of the extrusion means and the prevention of liquid carry over. It also enables the production of uniform flat tube of a constant wall thickness.

According to a third aspect of the present invention there is provided apparatus for use in extrusion of a blown film into a precipitation medium, the apparatus comprising a tubular member for containing precipitation medium and for receiving an extruded blown tube.

WO 00/23249

PCT/GB99/03439

7

According to a fourth aspect of the present invention there is provided a method of extruding blown film, the method comprising:

- extruding material through a die to form a tube;
- 5 maintaining the tube interior at a positive pressure;
- and
- passing the tube through a precipitation medium contained within a tubular member.

10 The aspects of the invention are useful in extrusion operations where a material, such as a cellulose\N-Methyl Morpholine N-Oxide (NMMO) melt solution, is extruded into a precipitation medium, which in the case of a cellulose/NMMO solution is water or aqueous NMMO solution, where the melt solution precipitates, typically to a solid

15 semi-gel state.

The tubular member may serve a number of useful functions: the member may be utilised to guide the extruded tube through the precipitation medium; and the member protects the extruded tube from disturbances in the

20 precipitation medium. As a result, it has been found that the presence of such a tubular member improves the uniformity of the tube wall thickness.

Preferably, the extruded material is a mixture of cellulose in tertiary amine-oxide, such as N-Methyl

25 Morpholine N-Oxide (NMMO) as discussed above.

Preferably also, the inner diameter of the tubular member is between 1.05 and 1.5 times the outer diameter of the extruded tube.

The precipitation medium will typically be provided as

30 a bath of liquid, with the precipitation liquid present both inside and surrounding the tube, and it is preferred that the tubular member is at least partially immersed in the liquid.

Preferably also, an air gap is provided between the

35 extrusion die and the bath of precipitation liquid, and by providing a positive pressure in the air gap within the extruded tube a blowing up or inflation of the tube

WO 00/23349

PCT/GB99/03439

8

results. Conveniently, this is achieved by introducing pressurised air into the air gap-within the tube.

Preferably also, the extruded tube moves downwardly through the tubular member. Most preferably, the tubular member is vertically oriented.

Preferably also, the tubular member is transparent, permitting the extruded tube to be viewed as it passes through the member.

The tubular member may have a solid wall, or may have a perforated or discontinuous wall.

Preferably also, the precipitation medium flows, preferably axially, between the extruded tube and the tubular member.

Preferably also, following precipitation, the extruded tube is flattened by pick-up members, typically pick-up rollers, and the tubular member is profiled to guide the extruded tube to the pick-up members.

According to a fifth aspect of the present invention there is provided an extruded cellulose product, such as a film or fibre, having a substantially uniform distribution of fine pores throughout its cross-sections.

The fine porous structure obtained is quite distinct from the structure found in cellulose films produced according to the viscose process. In the viscose process, a cross-section through the extruded film shows a relatively few large pores and these pores tend to be elongate with an aspect ratio in excess of 5 to 1. Generally, the pores are elliptical in cross-section. In contrast, the pore structure of the cellulose films of the present invention is quite different and shows a widespread distribution of fine pores substantially evenly distributed throughout the cross-section of the film. The pores tend to be somewhat irregular in shape but the aspect ratio tends to be less than 5 to 1 (e.g. in the range 1:1 - 1:5). This is believed to give rise to improved mechanical properties.

As determined by electron microscopy, the pore size of

WO 00/23249

PCT/GB99/03439

9

the extruded film varies dependent on whether the film has never been dried, is dried, or has been dried and rewetted. Surprisingly, the pore size tends to vary more markedly depending on these parameters than does the pore size of cellulose films produced from the conventional viscose process. In particular, it is found that the pore size of extruded never-dried cellulose film tends to lie in the region 10-500nm whereas the pore size of the dried film tends to lie in the region 5-50nm as determined by electron microscopy. In contrast, the spindle-like or elliptical voids of the viscose process tend to have a minor dimension of 5-150nm and a major dimension of 300-750nm.

Comparative pore dimensions have also been investigated using small angle X-ray (SAXS) techniques as described herein. It is noted that the pore volume of dried film tends to lie in the region 0.04-0.05% volume fraction (compared to 0.25 for the viscose process) the pore volume for rewetted film tends to lie in the range 0.05-2% (compared to 0.11 for viscose material). The pore dimension of dried material tends to lie in the range 2.0-2.5nm (compared to 2.4 for the viscose process) and the pore dimension for rewetted material is in the range 3.2-3.7 (compared to 2.0 for the viscose process). The pore internal surface area of dried film lies in the range 0.7-1.0m²/cm³ (compared to 4.3m²/cm³ for the viscose process) and for rewetted film tends to be in the region 5-25m²/cm³ (compared to about 2 for the viscose process). Thus, the material of the present invention tends to exhibit a multiplicity of fine pores compared to a relatively small number of large pores in the viscose process.

It is found that there is increased permeability through the cellulose film of the present invention which is typically in the range 225-500mg μ m ml/min cm² g (compared to a value of about 213 for the viscose process). The measurement methodology is given herein.

Finally, it is observed that the material of the present invention is less crystalline and exhibits a

WO 00/23249

PCT/GB99/03439

10

crystallinity typically in the range 35-42% (compared to the viscose process of 45%).

5 It is also observed that variations in the temperature of the precipitation bath (usually water or dilute NMMO solution) can lead to variations in the structure of the extruded cellulose film. In particular, higher temperatures (such as 20°C tend to favour large pore size, whereas lower temperatures (for example 10°C) tend to favour smaller pore sizes.

10 Figure 1 is a schematic diagram of a first embodiment of the invention showing a nitrogen blanket on top of melted dope in an extruder feeder hopper;

Figure 2 is a schematic view of a second embodiment of the invention for the production of cellulose tube and employing separate draw means and collapsing means;

Figure 3 is a schematic view of a third embodiment employing a combined draw means and collapsing means in the form of a pair of non-parallel moving belts;

20 Figure 4 is a schematic diagram of the overall extrusion process;

Figure 5 is an enlarged view of an area of Figure 4, and showing a tube-guiding pipe;

Figure 6 is a cross sectional morphology of never dried sample 7;

25 Figure 7 is the internal surface of sample 7;

Figure 8 is a cross sectional morphology of never dried sample 8;

Figure 9 is the internal surface of sample 8;

30 Figure 10 is a cross sectional morphology of never dried sample 14;

Figure 11 is the internal surface of sample 14;

Figure 12 is a cross sectional morphology of Lommel Standard code 023210, rewetted;

35 Figure 13 is the internal surface of Lommel Standard code 023210; and

Figure 14 shows an example of the pole values of sample 14.

WO 00/23249

PCT/GB99/03439

11

Figure 1 illustrates schematically apparatus for extruding a cellulose amine-oxide aqueous solution comprising a cellulose storage vessel 0 containing a cellulose amine-oxide solution 1 protected in the free space 2 above by a blanket of nitrogen at a slightly above-atmospheric pressure. The cellulose solution is fed to an extruder screw 5 driven by an extruder drive 4 and is then delivered by a gear pump 8 into an extrusion head 3. The cellulose amine-oxide solution is extruded in the form of a tube 6 via an air gap into a precipitation liquid 7 (for example water). The extruded tube is then finished in conventional manner.

Figure 2 shows schematically an extrusion means 101 including an extrusion die in annular form for extruding a cellulose tubular film 102 into a bath of precipitation liquid 106 via an air gap. In the case of an amine-oxide process, the cellulose solution for extrusion is a solution of cellulose and amine-oxide in water and the precipitation liquid is water or dilute amine-oxide solution. The extruded cellulose tube passes downwardly through the precipitation liquid until it encounters a collapsing device 103 in the form of a pair of opposed non-parallel plates coated with a low friction polymer (eg. PVDF). Each plate is inclined at an angle J of approximately 20° to the longitudinally machine direction (shown in a chain-dotted line). The collapsing means progressively collapses the tube into a flat form. The flattened tube is then drawn into the nip of a pair of rollers 104 which squeeze together the opposite sides of the flattened tube so as to form an effective seal and to supply sufficient pressure to the tube to maintain the extruded tube under a slight tension.

The distance H between the nip of the rollers and the initiation of collapsing of the tube walls can be varied experimentally until optimum results are achieved. Generally, the distance is in the region 10 to 100 centimetres.

WO 00/23249

PCT/GB99/03439

12

An amount 107 of precipitation liquid is also maintained inside the extruded cellulose tube by a means (shown in Figure 3) which maintains the level of liquid inside the tube approximately the same as that outside the tube and assists solidification of the interior of the extruded tube. An air space 108 is left above the precipitation liquid within the tube which is maintained at slightly above atmospheric pressure (eg. 0.1 to 10 mbar) to assist expansion of the extruded film in the transverse direction.

The effect of the nip rollers 104 is firstly to draw the extruded cellulose tube from the extrusion means thereby maintaining a slight tension in the tube which is found to minimise variations in thickness. Secondly, the nip rollers help define a closed volume of extrusion liquid 107 so that extrusion liquid is not carried further downstream with the cellulose film, which would otherwise necessitate cutting the film to release the liquid.

Figure 3 shows a further embodiment in which analogous parts are marked with the same reference numerals as in Figure 2. It differs from the embodiment shown in Figure 2 in that the function of the collapsing means and the roller draw means is combined in a pair of opposed non-parallel moving belt conveyors 105. Each conveyor comprises a belt 109 which passes around a nip roll 104 at one end and around an idler roll 110 of smaller diameter at the other end of its travel. The surface of the belts has an appropriate roughness for frictionally engaging and collapsing the tube walls before they are fed into the nip defined between the nip rollers 104. The internal run of each belt is inclined at an angle J of approximately 20° as before. The benefit of the moving belt conveyors is that the extruded cellulose film (which may still be somewhat delicate) is gently engaged by the moving conveyors and progressively fed into the nip of the rollers.

Figure 4 is an overall schematic diagram of the process and illustrates various processing conditions and

WO 00/23249

PCT/GB99/03439

13

Figure 5 is an enlarged view of Figure 4 showing guide rolls 224 which act as tube-guiding pipes. Dope (ie. cellulose-amine-oxide aqueous solution) at approximately 100°C is stored in storage vessel 212. It is transported via extrusion device 214 and an extrusion screw through pump 216 to extruder 201 where the cellulose tube is extruded as described previously. A constant volume of water 207 is maintained in the space between the nip rolls 204 and the extruder by control means (not shown). Input pump 218 and inlet line 219 together with outlet pump 20 and outlet line 211 continuously flush water through the contained volume 207. Clean water is introduced and a dilute solution of water and NMMO (in the case of a typical amine-oxide process) is discharged.

Similarly, a constant volume of air is maintained in the space 208 via a line 222 at a slightly supra-atmospheric pressure in the range 0.1 to 10.0mbar (for example 1mbar) to expand the tube transversely.

The extruded tube is collapsed and drawn down through nip rolls 204 as described previously and passes around a succession of guide rolls 224 within the water bath 206 to complete the cellulose solidification process. The flattened tube is then passed through a succession of water washing tanks (not shown) to remove any residual traces of amine-oxide; before plasticiser is applied to the outside of the tube and the tube is reeled for storage.

In this way, water is prevented by the nip rolls from being carried downstream, thus avoiding the need to cut the tube at regular intervals to release trapped water, as in prior art processes. The process allows flat cellulose tube of tightly-controlled dimensions to be produced.

Example 1 - showing the use of an inert gas blanket

A cellulose solution for extrusion was prepared by mixing cellulose pulp with an aqueous NMMO solution containing about 50% by weight NMMO. Water was removed from the mixture by applying heat and a reduced pressure.

WO 00/23249

PCT/GB99/03439

14

The water boiled off at approximately 70°C and the vapours were recovered in a condensor. Once the water content had been reduced to about 12%, the NMMO monohydrate formed and the cellulose began to dissolve in the NMMO monohydrate solution. A stabiliser was added to the solution to inhibit thermal degradation of NMMO. The temperature was then increased to about 95°C and all the cellulose fibres dissolved to form an extrusion solution. The pressure was further reduced to remove air bubbles from the cellulose solution. At a temperature of about 100°C the cellulose solution is a visco-elastic melt with a high viscosity and a pronounced elastic behaviour. The time to produce the cellulose solution was about 3 hours.

The cellulose solution was then stored in a storage vessel such as shown in Figure 4 and extruded through an annular die so as to form a NMMO-cellulose tube. The tube was passed into a precipitation bath containing a precipitation medium, such as water or aqueous NMMO solution. A positive pressure is applied into the air gap between the extrusion die and the precipitation bath so as to keep the tube inflated up. The inner volume of the tube is also kept filled up with precipitation liquid, the composition of which is controlled to be constant.

In the absence of a nitrogen blanket above the cellulose solution in the storage vessel, it was frequently noticed that the extruded tube was coloured brown-red and that the colour intensity varied between different extrusion runs. Moreover, even during a single extrusion run of 20 minutes the colour changed from light-red at the beginning of the run to dark brown-red at the end. However, when a nitrogen blanket was employed in the storage vessel according to the present invention, the amount of discolouration was reduced. Moreover, the pressurised nitrogen enhanced filling of the extruder screw.

WO 00/23249

PCT/GB99/03439

15

Example 2 - showing details of the extruded cellulose product

5 A cellulose solution for extrusion was prepared by mixing cellulose pulp with an aqueous NMMO solution containing about 50% by weight NMMO. Water was removed from the mixture by applying heat and a reduced pressure. The water boiled off at approximately 70°C and the vapours were recovered in a condenser. Once the water content had been reduced to about 12%, the NMMO monohydrate formed and
10 the cellulose began to dissolve in the NMMO monohydrate solution. A stabiliser was added to the solution to inhibit thermal degradation of NMMO. The temperature was then increased to about 95°C and all the cellulose fibres dissolved to form an extrusion solution. The pressure was
15 further reduced to remove air bubbles from the cellulose solution. At a temperature about 100°C, the cellulose solution is a visco-elastic melt with a high viscosity and a pronounced elastic behaviour. Time to produce the cellulose solution was about 3 hours.

20 The cellulose solution was then stored in a storage vessel and extruded through an annular die so as to form a NMMO-cellulose tube. The tube was passed into a precipitation bath containing a precipitation medium, such as water or aqueous NMMO solution. A positive pressure was
25 applied into the air gap between the extrusion die and the precipitation bath so as to keep the tube inflated. The inner volume of the tube was also kept filled up with precipitation liquid, the composition of which was controlled to be constant.

30 Measurements were carried out on the extruded film and photomicrographs thereof are shown in Figures 6 to 13. Figure 9 is an X-ray pole figure.

1. Transmission Electromicroscopy (TEM)

35 Transmission electromicroscopy was carried out according to well known procedures. The cross-sectional morphology of the NMMO casings is characterised by a

WO 00/23249

PCT/CB99/03439

16

network structure in which pores of varying size are embedded (see Figure 1). In general, the cross-sectional morphology can be divided into three zones, which do not have sharp boundaries and which tend to differ with respect to pore size and pore distribution, referred to as outer region, middle region and outer region. As a function of the processing conditions both symmetrical and asymmetrical morphologies can occur, as well as variations in dimensions of the regions and pore sizes (Table 1). It is also noted that precipitation bath temperatures have an effect on pore dimensions, lower temperatures (e.g. 10°C) giving generally smaller pores than higher temperatures (e.g. 20°C). This becomes evident by comparing Figures 6, 8 and 10 according to the present invention with Table 1 (viscose process for comparison). Reference to Table 1 also shows a comparison of cross-sectional morphologies of never-dried samples on the one hand and dried and rewetted samples on the other, which shows that the drying process causes irreversible changes in the pore size such that rewetting is not capable of re-establishing the original pore size of never dried samples.

The inner surface of the samples shows mainly an irregular network of aggregated fibrillar bundles without any preferred orientation (Figures 7, 9 and 11). The dimensions of the fibrillar bundles vary somewhat as a function of processing conditions, as does the surface roughness. The morphology of the viscose casings (Figures 12 and 13) by comparison is markedly different from those of the NMMO films of the present invention. Typical for the viscose casings is a symmetrical dense precipitation structure with immersed spindle-like voids, which are oriented in the machine direction of extrusion. Also, the surface structure of the viscose casings (Figure 13) is different from that of the NMMO films of the present invention. Characteristic of the viscose surfaces are micro and macro crazes as well as wrappings, preferentially oriented in the machine extrusion direction. Depending on

WO 00/23249

PCT/CB99/03439

17

processing conditions, variations of the pattern may occur.

2. X-Ray Texture Investigation

In order to determine the orientational state of the samples, pole figures were measured with an X-ray texture goniometer. The (1-10) and (110) pole figures were recorded in reflection and transmission geometries, respectively. Figure 14 shows an example of the (1-10) pole figure of Sample 14. From the half-width of the distribution curves obtained by cutting the pole figures in the machine (M) and transverse (T) directions the parameters of uniplanar orientation in the M-direction (Ogm) and in the transverse direction (Ogt) and the axial chain orientation parameters (OGa) were determined. The results for the air-dried samples are summarised in Table 2.

It can be seen from Table 2 that, as a function of the processing conditions, the parameter of uniplanar orientation (OGm) varies more strongly than (Ogt) in a transverse direction. The strongest variation is found for the axial chain orientation (OGa). For the sake of comparison, the corresponding parameters for a viscose sample are also given.

3. Wide Angle X-Ray Diffraction (WAXS)

WAXS investigations were performed in conventional manner with a wide angle X-ray diffractometer. From the corrected scattering curves of isotropised samples the degree of crystallinity (Xc) and the lattice distortion parameter (k) were calculated according to the Ruland-Vonk method. After peak separation, averaged lateral crystallite sizes (Dhkl) were determined from the half-width of the peaks with the help of the Scherrer equation. Results for the air-dried samples are summarised in Table 3. The variation in degree of crystallinity as a function of processing conditions is relatively low (36-41°) for the present cellulose film. On the other hand, the

WO 00/23249

PCT/GB99/03439

-18-

crystallinity of the conventional viscose casing is higher (about 45°). The lateral crystalline sizes do not show significant differences. Again, the values for the viscose sample are higher.

4. Small Angle X-Ray Investigations (SAXS)

SAXS investigations were performed using a Kratky camera with a position sensitive linear detector. According to the Porod scattering theory, from the corrected scattering curves in absolute units, the volume fraction (W_v) of the pores in colloidal dimensions, and a measure of the void diameter (I_v) (cord main intersection length) as well as the internal surface (O_{sp}) were calculated.

Table 4 shows the results of the SAXS investigations of dried and rewetted samples. It should be noted that the SAXS method records pores in colloidal dimensions (1 to about 100nm) only. Pore volume, average pore size and specific internal surface of the dried samples 3 and 4 do not differ significantly. After storage of these samples in water and careful drying by means of a solvent exchange procedure, pore volume and internal surface increase dramatically. This is more the case for sample 4 than for sample 3. For comparison, the effect is not present in viscose casings, and on the contrary pore volume and internal surface tend to decrease following such treatment.

Permeability

For selected samples from the experimental program, permeability measurements were carried out for which the results are shown in Table 5. Permeability is measured using a solution of $K_3Fe(CN)_6$. This shows that permeability for the NMMO casings of the present invention are higher than those for the comparison viscose casings.

WO 00/23249

-19-

PCT/GB99/03439

TABLE 1

Results of electron microscopy

Experiment	Precipitation bath temp. (°C)	cross-section	width of outer region (µm)	pore size (nm)				internal surface			
				outer region	middle	outer region	orientation	profile	bundle-dim. (nm)		
1, never dried	20	asymmetrical	2.5...4	10...100	400...500	10...175					
1, dried	20	asymmetrical		5...45	5...45	5...150	none	embossed	15...70		
2, never dried	10	symmetrical	2.5...3.5	10...60	10...100	10...60					
2, dried	10	symmetrical		5...30	5...50	5...30	none	flat	6.5...30		
3, never dried	20	symmetrical	1.5...2.3	10...60	10...150	10...60					
3, dried	20	symmetrical			5...30		none	flat	6.5...30		
4, never dried	10	symmetrical	1.5...2.5	10...60	10...100	10...60					
4, dried	10	symmetrical		5...30	5...25	5...30	none	flat	6.5...30		
5, never dried	10	asymmetric	2.5	10...70	10...120	10...100					
5, dried	10						none	flat	6.5...30		
6, never dried	20	asymmetric	1.5...2.6	10...120	10...350	10...80					
6, dried	20						none	embossed	15...70		
7, never dried	10	asymmetric	2.0...4.0	10...60	10...60	10...200					
7, dried	10						none	flat	6.5...30		
8, never dried	20	asymmetric	2.5...3.0	10...100	10...200	10...175					
8, dried	20						none	flat	15...50		
14, never dried	10	asymmetric	0.5...1.0	10...60	10...100	10...100					
14, dried	10						none	flat	15...30		
VISCOSE CASING		symmetrical		spindle-like voids a = 5...150, b = 300...750			strong in M-direction	flat w-shaped warping, grooves			

WO 00/23249

-20-

PCT/GB99/03439

TABLE 2

Orientational parameters from X-ray pole figure investigations

Sample dried	FWHM _M [degree]	Uniplanar OG _M	orientation FWHM _T [degree]	OG _T	Axial chain FWHM _A [degree]	orientat. OG _A
1	45.3	0.75	42.9	0.76	no orienta.	0
2	33.9	0.81	41.2	0.77	55	0.69
3	40.2	0.78	39.4	0.78	59	0.67
4	36.7	0.80	42.7	0.76	86	0.52
5	41.5	0.77	40.3	0.78	no orienta.	0
6	49.3	0.73	44.5	0.75	64	0.64
7	44.3	0.75	43.0	0.76	85	0.53
8	45.3	0.75	44.5	0.75	55	0.69
14	37.2	0.79	43.0	0.76	61	0.66
VISCOSE CASING	29.5	0.84	39.0	0.78	70	0.61

FWHM - full width at half maximum; M, T and A - machine, transverse and azimuthal directions; OG - orientational parameters

WO 00/23249

-21-

PCT/GB99/03439

TABLE 3

Degree of crystallinity and crystallite sizes of the air-dried samples as determined from X-ray investigations

Sample dried	x_c [%]	$k \cdot 10^3$ [nm ²]	$D_{(hkl)}$ [nm]		
			$D_{(110)}$	$D_{(10-1)}$	$D_{(002)}$
V1	39	2.6	3.9	4.6	3.3
V2	41	2.3	3.9	4.3	3.1
V3	39	2.1	3.6	4.1	3.4
V4	39	2.5	3.6	4.2	3.3
V5	38	2.4	3.9	4.3	3.2
V6	37	2.5	3.7	4.3	3.5
V7	36	2.3	3.7	4.0	3.4
V8	41	2.2	3.6	4.3	3.4
V14	36	2.2	3.9	4.1	3.5
VISCOSE CASING	45	2.3	4.5	4.5	3.6

 x_c - degree of crystallinity, k - disorder parameter, D_{hkl} - crystallite dimensions

WO 00/23249

-22-

PCT/GB99/03439

TABLE 4

Table contains the results of the SAXS investigations of the dried and rewetted samples. It should be considered that the SAXS method records pores in colloidal dimensions (1 to about 100 nm) only.

Sample	w _v [%]	L _v [nm]	O _{int} [m ² /cm ³]
3, dried	0.04	2.4	0.8
3, rewetted	0.58	3.3	7.0
4, dried	0.05	2.1	0.9
4, rewetted	1.97	3.6	22.2
VISCOSE CASING DRIED	0.25	2.4	4.3
VISCOSE CASING REWETTED	0.11	2.0	2.0

w_v - volume fraction of pores, L_v - averaged pore dimensions, O_{int} - specific internal surface

WO 00/23249

-23-

PCT/GB99/03439

TABLE 5Permeability values of cellulose fibres (substance $K_2Fe(CN)_6$)

Experiment	permeation value (mg μ m ml/(min cm ² g))
7	394
8	331
9	362
14	379
17	276
VISCOSE CASING	213

WO 00/23249

PCT/GB99/03439

-24-

CLAIMS

1. A process for extruding a solution of cellulose, water and an amine-oxide, which comprises

- 5 - providing a closed vessel containing said cellulose solution;
- providing an inert gas blanket above the cellulose solution in the vessel; and
- 10 - delivering the cellulose solution to an extrusion means for extrusion thereof.

2. Apparatus for the production of extruded blown cellulose film from a solution of cellulose, water and an amine-oxide, which comprises

- 15 - extrusion means for continuously extruding a cellulose solution to produce a cellulose film;
- precipitation means for solidifying the extruded cellulose film;
- draw means positioned downstream of the extrusion means for continuously drawing the extruded
- 20 cellulose film from the extrusion means; and
- a tubular member for containing the precipitation means and for receiving an extruded blown tube.

3. A method of extruding blown film, the method comprising:

- 25 extruding material through a die to form a tube;
- maintaining the tube interior at a positive pressure;
- and
- passing the tube through a precipitation medium contained within a tubular member.

30 4. An extruded cellulose film having a substantially uniform distribution of fine pores throughout its cross-section.

5. A cellulosic film as in claim 4 produced by extruding a dissolved cellulose solution in N-Methyl Morpholine N-

WO 00/23249

PCT/GB99/03439

-25-

oxide monohydrate.

6. A cellulosic film as in claim 4 with a permeability in the range 225-500 mg μm ml/min cm^2g .

- 5 7. A cellulosic film as in claim 4 with a crystalline cellulose structure in the range 36-41% as measured with wide angle X-ray defraction.

WO 00/23249

1 / 13

PCT/GB99/03439




FIGURE 1: : NITROGEN BLANKET ON TOP OF MELTED DOPE IN EXTRUDER FEEDER HOPPER

WO 00/23249

2 / 13

PCT/GB99/03439




FIGURE 2: PLATE SLIDE COLLAPSORS AND BOTTOM SQUEEZE ROLLS




FIGURE 3: MOVING BELT COLLAPSORS COMBINED WITH BOTTOM SQUEEZE ROLLS

SUBSTITUTE SHEET (RULE 26)

WO 00/23249

3 / 13

PCT/GB99/03439




FIGURE 4

SUBSTITUTE SHEET (RULE 26)

09/830044

WO 00/23249

4 / 13

PCT/GB99/03439




FIGURE 5


09/830044

WO 00/23249

5 / 13

PCT/GB99/03439

FIGURE 6



Cross sectional morphology of never dried sample 7

SUBSTITUTE SHEET (RULE 26)


09/830044

WO 00/23249

6 / 13

PCT/GB99/03439

FIGURE 7



Internal surface of sample 7

SUBSTITUTE SHEET (RULE 26)


09/830044

WO 00/23249

7 / 13

PCT/GB99/03439

FIGURE 8



Cross sectional morphology of never dried sample 8

SUBSTITUTE SHEET (RULE 26)


09/830044

WO 00/23249

8 / 13

PCT/GB99/03439

FIGURE 9



Internal surface of sample 8


SUBSTITUTE SHEET (RULE 26)

WO 00/23249

9 / 13

PCT/GB99/03439

FIGURE 10



Cross sectional morphology of never dried sample 14

SUBSTITUTE SHEET (RULE 26)


09/830044

WO 00/23249

10 / 13

PCT/GB99/03439

FIGURE 11



Internal surface of sample 14

SUBSTITUTE SHEET (RULE 26)

09/830044

WO 00/23249

11 / 13

PCT/GB99/03439

FIGURE 12

outer region



centre



outer region

Cross sectional morphology of Lommel Standard code 023210, rewetted

SUBSTITUTE SHEET (RULE 26)


09/830044

WO 00/23249

12 / 13

PCT/GB99/03439

FIGURE 13



Internal surface of Lommel Standard code 023210


SUBSTITUTE SHEET (RULE 26)

09/830044

WO 00/23249

13 / 13

PCT/GB99/03439

FIGURE 14

SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference DCM/GW/CB/P10099PC	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/GB99/03439	International filing date (day/month/year) 18/10/1999	Priority date (day/month/year) 21/10/1998
International Patent Classification (IPC) or national classification and IPC B29C47/00		
Applicant DEVRO PLC et al.		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.



2. This REPORT consists of a total of 7 sheets, including this cover sheet.

- ☐ This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☒ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☒ Certain defects in the international application
- VIII ☐ Certain observations on the international application

Date of submission of the demand 11/05/2000	Date of completion of this report 08.02.2001
Name and mailing address of the international preliminary examining authority:  European Patent Office - P.B. 5818 Patentlaan 2 NL-2280 HV Rijswijk - Pays Bas Tel. +31 70 340 - 2040 Tx: 31 651 epo nl Fax: +31 70 340 - 3016	Authorized officer Van Nieuwenhuize, O Telephone No. +31 70 340 3435 

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/GB99/03439

I. Basis of the report

1. This report has been drawn on the basis of *(substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments (Rules 70.16 and 70.17).):*

Description, pages:

1-23 as originally filed

Claims, No.:

1-7 as originally filed

Drawings, sheets:

1/13-13/13 as originally filed

2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.

These elements were available or furnished to this Authority in the following language: , which is:

- ☐ the language of a translation furnished for the purposes of the international search (under Rule 23.1(b)).
- ☐ the language of publication of the international application (under Rule 48.3(b)).
- ☐ the language of a translation furnished for the purposes of international preliminary examination (under Rule 55.2 and/or 55.3).

3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:

- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.

4. The amendments have resulted in the cancellation of:

- ☐ the description, pages:
- ☐ the claims, Nos.:

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/GB99/03439

☐ the drawings, sheets:

5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.)

6. Additional observations, if necessary:

IV. Lack of unity of invention

1. In response to the invitation to restrict or pay additional fees the applicant has:

- ☐ restricted the claims.
☐ paid additional fees.
☐ paid additional fees under protest.
☒ neither restricted nor paid additional fees.

2. ☐ This Authority found that the requirement of unity of invention is not complied and chose, according to Rule 68.1, not to invite the applicant to restrict or pay additional fees.

3. This Authority considers that the requirement of unity of invention in accordance with Rules 13.1, 13.2 and 13.3 is

- ☐ complied with.
☒ not complied with for the following reasons:
see separate sheet

4. Consequently, the following parts of the international application were the subject of international preliminary examination in establishing this report:

- ☐ all parts.
☒ the parts relating to claims Nos. 1.

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes:	Claims
	No:	Claims 1
Inventive step (IS)	Yes:	Claims
	No:	Claims 1

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/GB99/03439

Industrial applicability (IA) Yes: Claims 1
 No: Claims

2. Citations and explanations
see separate sheet

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:
see separate sheet

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/GB99/03439

Re Item IV

Lack of unity of invention

1. The separate groups of claimed inventions are:
 - (1) Claim 1 storing a solution of cellulose in amine-oxide and water under an inert gas blanket prior to extrusion
 - (2) Claims 2, 3 Method and apparatus for cellulose film blowing
 - (3) Claims 4 - 7 extruded porous cellulose film
2. These groups are not so linked as to form a single general inventive concept (Rule 13.1 PCT) for the following reasons as already indicated by the International Searching Authority and set out in the invitation to restrict or to pay additional fees (PCT Article 34(3)(a) and Rule 68.2):
 - (1) The special technical feature of independent claim 1 over DE-A-4219658, cf. examples 5 and 6 is the provision of an inert gas blanket above the cellulose solution. The underlying problem is the prevention of thermal degradation, cf. page 2, line 9 - 11 and page 3, lines 1 and 2.
 - (2) Independent method claim 3 and apparatus claim 2 do not contain this special technical feature. The problem underlying independent claims 3 and 2 is to prevent undesirable stretching and variations in thickness and diameter, cf. page 2, line 36 and 37 and page 3, lines 1 and 2. Thus the claims 1 and claims 2, 3 do not have common special technical features while they solve different problems.

WO-A-9535340, cf. examples 1, 3, discloses a method of blowing cellulose film from which the subject-matter of both claims 2 and 3 differs in a tubular member containing the precipitation means, which is the special technical feature. The problem underlying independent claims 3 and 2 is to prevent

undesirable stretching and variations in thickness and diameter, cf. page 2, line 36 and 37 and page 3, lines 1 and 2.

- (3) The special technical feature of claim 4 over WO-A-9535340 or DE-A-4219658 is a substantially uniform distribution of fine pores throughout the film's cross-section. Therefore claim 4 on one side and claims 1, 2 or 3 on the other side do not have common special technical features and have different underlying problems.

Re Item V

Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Reference is made to the following documents:

D1: US-A-4416698

D2: US-A-4196282

2. Documents D1 (cf. example 1, figure 1) and D2 (cf. example 2) both disclose a process for extruding a solution of cellulose, water and an amine-oxide, which comprises providing a closed vessel containing said cellulose solution, providing an inert gas blanket above the cellulose solution in the vessel, and delivering the cellulose solution to an extrusion means for extrusion thereof, for which reason the subject-matter of claim 1 lacks novelty.

Therefore claim 1 does not meet the requirements of Article 33(2) PCT.

Consequently claim 1 does not meet the requirements of Article 33(3) PCT.

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/GB99/03439

Re Item VII

Certain defects in the international application

1. The features of the claims should have been provided with reference signs placed in parentheses (Rule 6.2(b) PCT).

2. In order to meet the requirements of Rule 5.1(a)(ii) PCT, the relevant background art in respect of the subject-matter of claim 1, which is disclosed in the documents D1 and D2, should have been mentioned in the description, and these documents should be identified therein.


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B29C 47/00, 47/10, 55/28, B01D 71/10, C08B 1/00, C08J 5/18		A2	(11) International Publication Number: WO 00/23249
(21) International Application Number: PCT/GB99/03439		(43) International Publication Date: 27 April 2000 (27.04.00)	
(22) International Filing Date: 18 October 1999 (18.10.99)		(74) Agents: MCCALLUM, William, Potter et al.; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).	
(30) Priority Data: 9823080.8 21 October 1998 (21.10.98) GB 9823081.6 21 October 1998 (21.10.98) GB 9823083.2 21 October 1998 (21.10.98) GB 9823085.7 21 October 1998 (21.10.98) GB		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(71) Applicants (for all designated States except US): DEVRO PLC [GB/GB]; Moddiesburn, Chryston, Glasgow G69 0JE (GB). FRAUNHOFER-GESELLSCHAFT ZUR FORDERUNG DER ANGEWANDTEN FORSCHUNG E.V. [DE/DE]; Leonrodstrasse 54, D-80636 Munich (DE). (72) Inventors; and (75) Inventors/Applicants (for US only): BECKERS, Stefan, D. [BE/BE]; Panovenstraat 19, B-3941 Hechtel-Eskel (BE). WEIGEL, Peter [DE/DE]; Seelenbinder 3B, D-14532 Kleinmachnow (DE). FINK, Hans-Peter [DE/DE]; Kiefernweg 7, D-74513 Teltow (DE). DOSZ, Michael [DE/DE]; Hildburghauser Strasse 191A, D-12209 Berlin (DE). PURZ, Hans-Joachim [DE/DE]; Mairenfelder Anger 30, D-14513 Teltow (DE).		Published Without international search report and to be republished upon receipt of that report.	

(54) Title: CELLULOSE EXTRUSION

(57) Abstract

A process and apparatus used in cellulose extrusion is disclosed. In particular, the process discloses using an inert gas blanket above a cellulose solution wherein the inert gas blanket reduces any undesirable colour variations in the extruded product. Furthermore, the apparatus discloses draw means positioned downstream of the extrusion means to continuously draw the extruded cellulose film from the extrusion means. Apparatus is also disclosed wherein a tubular member is used to receive an extruded blown tube. The product formed using the process and apparatus described herein which has a substantially uniform distribution of fine pores throughout its cross-section is also discussed.




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B29C 47/00, 47/10, 55/28, B01D 71/10, C08B 1/00, C08J 5/18 // B29K 1:00		A3	(11) International Publication Number: WO 00/23249
			(43) International Publication Date: 27 April 2000 (27.04.00)
(21) International Application Number: PCT/GB99/03439		(74) Agents: MCCALLUM, William, Potter et al.; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).	
(22) International Filing Date: 18 October 1999 (18.10.99)			
(30) Priority Data:		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
9823080.8 21 October 1998 (21.10.98) GB 9823081.6 21 October 1998 (21.10.98) GB 9823083.2 21 October 1998 (21.10.98) GB 9823085.7 21 October 1998 (21.10.98) GB			
(71) Applicants (for all designated States except US): DEVRO PLC [GB/GB]; Moddiesburn, Chryston, Glasgow G69 0JE (GB). FRAUNHOFER-GESELLSCHAFT ZUR FORDERUNG DER ANGEWANDTEN FORSCHUNG E.V. [DE/DE]; Leonrodstrasse 54, D-80636 Munich (DE).			
(72) Inventors; and		Published	
(75) Inventors/Applicants (for US only): BECKERS, Stefan, D. [BE/BE]; Panovenstraat 19, B-3941 Hechtel-Eskel (BE). WEIGEL, Peter [DE/DE]; Seelenbinder 3B, D-14532 Kleinmachnow (DE). FINK, Hans-Peter [DE/DE]; Kiefernweg 7, D-74513 Teltow (DE). DOSZ, Michael [DE/DE]; Hildburghauser Strasse 191A, D-12209 Berlin (DE). PURZ, Hans-Joachim [DE/DE]; Mairfelder Anger 30, D-14513 Teltow (DE).		With international search report.	
		(88) Date of publication of the international search report: 24 August 2000 (24.08.00)	

(54) Title: CELLULOSE EXTRUSION

(57) Abstract

A process and apparatus used in cellulose extrusion is disclosed. In particular, the process discloses using an inert gas blanket above a cellulose solution wherein the inert gas blanket reduces any undesirable colour variations in the extruded product. Furthermore, the apparatus discloses draw means positioned downstream of the extrusion means to continuously draw the extruded cellulose film from the extrusion means. Apparatus is also disclosed wherein a tubular member is used to receive an extruded blown tube. The product formed using the process and apparatus described herein which has a substantially uniform distribution of fine pores throughout its cross-section is also discussed.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

In: International Application No
PCT/GB 99/03439

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B29C47/00 B29C47/10 B29C55/28 B01D71/10 C08B1/00
C08J5/18 //B29K1:00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B29C C08B C08J B01D A22C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 416 698 A (MCCORSLEY III CLARENCE C) 22 November 1983 (1983-11-22) figure 1; example 1 ----	1
X	US 4 196 282 A (FRANKS NEAL E ET AL) 1 April 1980 (1980-04-01) column 8, line 50 - line 65; example 2 ----	1
X	EP 0 822 201 A (DAICEL CHEM) 4 February 1998 (1998-02-04) page 6, line 1 - line 14 ----	1
X	EP 0 807 460 A (AKZO NOBEL NV) 19 November 1997 (1997-11-19) claims 1,36 ----- -/-	4,5

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

12 May 2000

Date of mailing of the international search report

05.05.00

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Van Nieuwenhuize, O

INTERNATIONAL SEARCH REPORT

In International Application No

PCT/GB 99/03439

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 042 517 A (AKZO GMBH) 30 December 1981 (1981-12-30) page 4, paragraph 2 - paragraph 4 ---	4,5
X	US 3 853 448 A (YAZAWA M) 10 December 1974 (1974-12-10) claim 1; figure 1 ---	2,3
X	US 3 950 467 A (YAZAWA MASAHIDE ET AL) 13 April 1976 (1976-04-13) claims 1,2 ---	2,3
X	US 3 280 234 A (R.O. OSBORN) 18 October 1966 (1966-10-18) column 4, line 51 - line 54 ---	3
A ✓	DD 218 104 A (THUERINGISCHES INST FUER TEXTI) 30 January 1985 (1985-01-30) examples 1-9 ---	1
A	US 3 447 939 A (JOHNSON DEE LYNN) 3 June 1969 (1969-06-03) claim 1 ---	1
A	PATENT ABSTRACTS OF JAPAN vol. 013, no. 178 (M-819), 26 April 1989 (1989-04-26) & JP 01 009715 A (FUJIKURA LTD), 13 January 1989 (1989-01-13) abstract ---	1
A	PATENT ABSTRACTS OF JAPAN vol. 014, no. 215 (C-0716), 8 May 1990 (1990-05-08) & JP 02 049005 A (TORAY IND INC), 19 February 1990 (1990-02-19) abstract ---	1
A ✓	EP 0 528 257 A (ALBRIGHT & WILSON) 24 February 1993 (1993-02-24) column 4, line 23 - line 37; figure 2 ---	1
A ✓	EP 0 375 405 A (MITSUI PETROCHEMICAL IND) 27 June 1990 (1990-06-27) page 8, line 51 - line 53 page 10, line 36 - line 38; figure 2 ---	1
A	US 4 144 080 A (MCCORSLEY III CLARENCE C) 13 March 1979 (1979-03-13) column 2, line 9 - line 60; figure 2 ---	1
A.	DE 42 19 658 A (THUERINGISCHES INST FUER TEXTI) 23 December 1993 (1993-12-23) page 3, line 61 - line 68 ---	1
	-/--	

INTERNATIONAL SEARCH REPORT

In International Application No

PCT/GB 99/03439

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A ✓	WO 95 35340 A (FRAUNHOFER GES FORSCHUNG ;WEIGEL PETER (DE); FINK HANS PETER (DE);) 28 December 1995 (1995-12-28) examples 1,3 ---	1
A	US 3 767 756 A (BLADES H) 23 October 1973 (1973-10-23) figure 2 ---	2
A	US 1 654 253 A (W.F. HENDERSON) 27 December 1927 (1927-12-27) figure 1 ---	2
A ✓	EP 0 483 562 A (LINDE AG) 6 May 1992 (1992-05-06) claims 1,8; figure 1 ---	2
A	EP 0 662 283 A (VISKASE CORP) 12 July 1995 (1995-07-12) claim 1 ---	2,3
A	WO 96 20301 A (FRAUNHOFER GES FORSCHUNG ;AKZO NOBEL FASER AG (DE); WEIGEL PETER () 4 July 1996 (1996-07-04) claim 1 ---	4
A	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 04, 30 April 1996 (1996-04-30) & JP 07 330945 A (ASAHI CHEM IND CO LTD), 19 December 1995 (1995-12-19) abstract ---	4
A	WO 97 37392 A (COURTAULDS FIBRES HOLDINGS LTD ;ASKEW GREGORY JAMES (GB); LAW STEP) 9 October 1997 (1997-10-09) claims 1,12-15; figure 1 ---	4
A	DE 195 15 137 A (THUERINGISCHES INST FUER TEXTIL) 31 October 1996 (1996-10-31) claim 1 ---	5
A	WO 98 42492 A (SCHLOSSNIKL CHRISTIAN ;GSPALTL PETER (AT); KOFLER ALOIS (AT); CHEM) 1 October 1998 (1998-10-01) claims 1-12 ---	3-6
P,A	EP 0 899 076 A (KALLE NALO GMBH & CO KG) 3 March 1999 (1999-03-03) the whole document -----	3-6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/GB 99/03439

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claim : 1

storing a solution of cellulose in amine-oxide and water
under an inert gas blanket prior to extrusion

2. Claims: 2, 3

Method and apparatus for cellulose film blowing

3. Claims: 4-7

extruded porous cellulose film

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03439

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4416698 A	22-11-1983	US 4246221 A	20-01-1981
		US 4144080 A	13-03-1979
		AT 387792 B	10-03-1989
		AT 268679 A	15-08-1988
		AU 4593779 A	04-09-1980
		BE 875323 A	04-10-1979
		CA 1141913 A	01-03-1983
		DD 142898 A	16-07-1980
		DE 2913589 A	11-09-1980
		ES 479450 A	16-10-1979
		FR 2450293 A	26-09-1980
		GB 2043525 A, B	08-10-1980
		IN 154748 A	15-12-1984
		IN 154757 A	15-12-1984
		IT 1115165 B	03-02-1986
		JP 1308043 C	13-03-1986
		JP 55118928 A	12-09-1980
		JP 60028848 B	06-07-1985
		NL 7902782 A	04-09-1980
		NO 791041 A	03-09-1980
		SE 444191 B	24-03-1986
		SE 7902733 A	03-09-1980
		TR 20668 A	21-04-1982
		AR 225004 A	15-02-1982
		AT 364900 B	25-11-1981
		AT 543978 A	15-04-1981
		AU 3814778 A	24-01-1980
		BE 868737 A	03-11-1978
		BR 7804794 A	03-04-1979
		CA 1116808 A	26-01-1982
		DD 140356 A	27-02-1980
		DE 2830685 A	15-02-1979
		DK 330978 A	27-01-1979
		ES 472037 A	01-02-1979
		FI 782170 A, B,	27-01-1979
		FR 2398774 A	23-02-1979
		GB 2001320 A, B	31-01-1979
		GR 64549 A	12-04-1980
		IN 147905 A	09-08-1980
		IT 1096905 B	26-08-1985
		JP 1048126 C	28-05-1981
		JP 54024963 A	24-02-1979
		JP 55041693 B	25-10-1980
		LU 79932 A	07-12-1978
		NL 7807421 A	30-01-1979
		NO 782556 A, B,	29-01-1979
		SE 445926 B	28-07-1986
		SE 7808039 A	27-01-1979
		TR 20127 A	01-09-1980
		ZA 7803707 A	25-07-1979
US 4196282 A	01-04-1980	US 4145532 A	20-03-1979
		AT 376986 B	25-01-1985
		AT 843478 A	15-06-1984
		AU 4181078 A	31-05-1979
		CA 1111206 A	27-10-1981
		DE 2848471 A	07-06-1979
		DK 525678 A	26-05-1979

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/GB 99/03439

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4196282 A		ES 476575 A	16-12-1979
		FI 783597 A,B,	26-05-1979
		FR 2423559 A	16-11-1979
		GB 2010279 A,B	27-06-1979
		IN 150398 A	25-09-1982
		IT 1101441 B	28-09-1985
		JP 1123841 C	30-11-1982
		JP 54099148 A	04-08-1979
		JP 57011566 B	05-03-1982
		LU 80571 A	16-05-1979
		NL 7811571 A	29-05-1979
		NO 783963 A	28-05-1979
		RO 77343 A	17-08-1981
		SE 443793 B	10-03-1986
		SE 7812131 A	26-05-1979
		TR 20125 A	19-09-1980
		US 4256613 A	17-03-1981
		US 4284545 A	18-08-1981
		BE 871895 A	01-03-1979
		ES 475378 A	01-12-1979
		JP 57085823 A	28-05-1982
		ZA 7805952 A	26-09-1979
EP 0822201 A /	04-02-1998	JP 10045803 A	17-02-1998
		CN 1176253 A	18-03-1998
		US 5977347 A	02-11-1999
		US 5856468 A	05-01-1999
EP 0807460 A /	19-11-1997	JP 10052630 A	24-02-1998
		US 6019925 A	01-02-2000
EP 0042517 A /	30-12-1981	DE 3021943 A	21-01-1982
		AT 7206 T	15-05-1984
		AU 7147981 A	17-12-1981
		BR 8103677 A	02-03-1982
		CA 1171615 A	31-07-1984
		DD 159527 A	16-03-1983
		DK 254081 A	13-12-1981
		ES 502962 D	01-04-1982
		ES 8203629 A	16-07-1982
		FI 811840 A	13-12-1981
		GR 74574 A	29-06-1984
		JP 1771019 C	30-06-1993
		JP 4060692 B	28-09-1992
		JP 57024606 A	09-02-1982
		NO 811958 A	22-03-1982
		PT 73167 A,B	01-07-1981
		ZA 8103985 A	30-06-1982
US 3853448 A	10-12-1974	JP 48040855 A	15-06-1973
		DE 2244250 A	29-03-1973
		FR 2157796 A	08-06-1973
		IT 969444 B	30-03-1974
US 3950467 A	13-04-1976	JP 882949 C	30-09-1977
		JP 49111967 A	24-10-1974
		JP 52009224 B	15-03-1977
		DE 2409105 A	05-09-1974

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. lional Application No

PCT/GB 99/03439

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3950467 A		FR 2218986 A GB 1410573 A IT 1003583 B	20-09-1974 22-10-1975 10-06-1976
US 3280234 A	18-10-1966	BE 620293 A FR 1332817 A NL 280994 A US 3423400 A	16-12-1963 21-01-1969
DD 218104 A	30-01-1985	NONE	
US 3447939 A	03-06-1969	BE 703203 A BE 703240 A DE 1694047 A DE 1694048 A FR 1546629 A FR 1556993 A GB 1144048 A GB 1144759 A US 3508941 A	15-01-1968 15-01-1968 30-10-1969 05-02-1970 14-02-1969 28-04-1970
JP 01009715 A	13-01-1989	JP 1922560 C JP 6045168 B	07-04-1995 15-06-1994
JP 02049005 A	19-02-1990	JP 2745552 B	28-04-1998
EP 0528257 A	24-02-1993	GB 2258656 A AT 128404 T CA 2075779 A DE 69205102 D DE 69205102 T JP 5208417 A MX 9204732 A RU 2068291 C US 5351596 A ZA 9205825 A	17-02-1993 15-10-1995 16-02-1993 02-11-1995 18-04-1996 20-08-1993 01-07-1993 27-10-1996 04-10-1994 18-03-1993
EP 0375405 A	27-06-1990	JP 2165911 A JP 2625184 B JP 2165912 A JP 2625185 B JP 2165915 A JP 2625186 B JP 2165913 A JP 2625187 B JP 2165914 A AT 134558 T CA 2005995 C CA 2005995 A DE 68925804 D DE 68925804 T ES 2086321 T HK 194096 A KR 9210136 B SG 42317 A US 5034177 A US 5286187 A	26-06-1990 02-07-1997 26-06-1990 02-07-1997 26-06-1990 02-07-1997 26-06-1990 02-07-1997 26-06-1990 15-03-1996 22-03-1994 20-06-1990 04-04-1996 06-02-1997 01-07-1996 01-11-1996 16-11-1992 15-08-1997 23-07-1991 15-02-1994

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03439

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4144080	A	13-03-1979	AR 225004 A	15-02-1982
			AT 364900 B	25-11-1981
			AT 543978 A	15-04-1981
			AU 3814778 A	24-01-1980
			BE 868737 A	03-11-1978
			BR 7804794 A	03-04-1979
			CA 1116808 A	26-01-1982
			DD 140356 A	27-02-1980
			DE 2830685 A	15-02-1979
			DK 330978 A	27-01-1979
			ES 472037 A	01-02-1979
			FI 782170 A,B,	27-01-1979
			FR 2398774 A	23-02-1979
			GB 2001320 A,B	31-01-1979
			GR 64549 A	12-04-1980
			IN 147905 A	09-08-1980
			IT 1096905 B	26-08-1985
			JP 1048126 C	28-05-1981
			JP 54024963 A	24-02-1979
			JP 55041693 B	25-10-1980
			LU 79932 A	07-12-1978
			NL 7807421 A	30-01-1979
			NO 782556 A,B,	29-01-1979
			SE 445926 B	28-07-1986
			SE 7808039 A	27-01-1979
			TR 20127 A	01-09-1980
			US 4416698 A	22-11-1983
			ZA 7803707 A	25-07-1979
DE 4219658	A	23-12-1993	AT 173770 T	15-12-1998
			DE 4308524 C	22-09-1994
			EP 0574870 A	22-12-1993
			US 5417909 A	23-05-1995
WO 9535340	A	28-12-1995	DE 4421482 A	21-12-1995
			EP 0766709 A	09-04-1997
			JP 10501570 T	10-02-1998
US 3767756	A	23-10-1973	NONE	
US 1654253	A	27-12-1927	NONE	
EP 0483562	A	06-05-1992	DE 4034234 A	30-04-1992
EP 0662283	A	12-07-1995	US 5451364 A	19-09-1995
			US 5658524 A	19-08-1997
WO 9620301	A	04-07-1996	DE 4446491 C	27-06-1996
			AU 4326996 A	19-07-1996
			EP 0799332 A	08-10-1997
			US 5993710 A	30-11-1999
JP 07330945	A	19-12-1995	NONE	
WO 9737392	A	09-10-1997	AU 2039197 A	22-10-1997
			BR 9708490 A	03-08-1999
			CN 1215505 A	28-04-1999
			EP 0891640 A	20-01-1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

In: International Application No

PCT/GB 99/03439

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19515137 A	31-10-1996	WO 9634037 A	31-10-1996
WO 9842492 A	01-10-1998	AT 404595 B	28-12-1998
		AT 49597 A	15-05-1998
		AU 6385098 A	20-10-1998
		CA 2255638 A	01-10-1998
		CN 1219148 T	09-06-1999
		EP 0904187 A	31-03-1999
		NO 985399 A	20-11-1998
EP 0899076 A	03-03-1999	DE 19737113 A	04-03-1999
		US 6033618 A	07-03-2000

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference DCM/GW/CB/P10099PC	FOR FURTHER ACTION see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. PCT/GB 99/ 03439	International filing date (day/month/year) 18/10/1999	(Earliest) Priority Date (day/month/year) 21/10/1998
Applicant DEVRO PLC et al.		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 6 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

- a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

- b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

☐ contained in the international application in written form.

☐ filed together with the international application in computer readable form.

☐ furnished subsequently to this Authority in written form.

☐ furnished subsequently to this Authority in computer readable form.

☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ Certain claims were found unsearchable (See Box I).

3. ☒ Unity of invention is lacking (see Box II).

4. With regard to the title,

☒ the text is approved as submitted by the applicant.

☐ the text has been established by this Authority to read as follows:

5. With regard to the abstract,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No. 4

☐ as suggested by the applicant.

☒ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

☐ None of the figures.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/GB 99/03439

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claim : 1

storing a solution of cellulose in amine-oxide and water
under an inert gas blanket prior to extrusion

2. Claims: 2, 3

Merthod and apparatus for cellulose film blowing

3. Claims: 4-7

extruded porous cellulose film

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/03439

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B29C47/00 B29C47/10 B29C55/28 B01D71/10 C08B1/00
C08J5/18 //B29K1:00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B29C C08B C08J B01D A22C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 416 698 A (MCCORSLEY III CLARENCE C) 22 November 1983 (1983-11-22) figure 1; example 1 ----	1
X	US 4 196 282 A (FRANKS NEAL E ET AL) 1 April 1980 (1980-04-01) column 8, line 50 - line 65; example 2 ----	1
X	EP 0 822 201 A (DAICEL CHEM) 4 February 1998 (1998-02-04) page 6, line 1 - line 14 ----	1
X	EP 0 807 460 A (AKZO NOBEL NV) 19 November 1997 (1997-11-19) claims 1,36 ----- -/--	4,5



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

12 May 2000

Date of mailing of the international search report

05.06.00

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van Nieuwenhuize, O

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 042 517 A (AKZO GMBH) 30 December 1981 (1981-12-30) page 4, paragraph 2 - paragraph 4 ----	4,5
X	US 3 853 448 A (YAZAWA M) 10 December 1974 (1974-12-10) claim 1; figure 1 ----	2,3
X	US 3 950 467 A (YAZAWA MASAHIDE ET AL) 13 April 1976 (1976-04-13) claims 1,2 ----	2,3
X	US 3 280 234 A (R.O. OSBORN) 18 October 1966 (1966-10-18) column 4, line 51 - line 54 ----	3
A	DD 218 104 A (THUERINGISCHES INST FUER TEXTI) 30 January 1985 (1985-01-30) examples 1-9 ----	1
A	US 3 447 939 A (JOHNSON DEE LYNN) 3 June 1969 (1969-06-03) claim 1 ----	1
A	PATENT ABSTRACTS OF JAPAN vol. 013, no. 178 (M-819), 26 April 1989 (1989-04-26) & JP 01 009715 A (FUJIKURA LTD), 13 January 1989 (1989-01-13) abstract ----	1
A	PATENT ABSTRACTS OF JAPAN vol. 014, no. 215 (C-0716), 8 May 1990 (1990-05-08) & JP 02 049005 A (TORAY IND INC), 19 February 1990 (1990-02-19) abstract ----	1
A	EP 0 528 257 A (ALBRIGHT & WILSON) 24 February 1993 (1993-02-24) column 4, line 23 - line 37; figure 2 ----	1
A	EP 0 375 405 A (MITSUI PETROCHEMICAL IND) 27 June 1990 (1990-06-27) page 8, line 51 - line 53 page 10, line 36 - line 38; figure 2 ----	1
A	US 4 144 080 A (MCCORSLEY III CLARENCE C) 13 March 1979 (1979-03-13) column 2, line 9 - line 60; figure 2 ----	1
A	DE 42 19 658 A (THUERINGISCHES INST FUER TEXTI) 23 December 1993 (1993-12-23) page 3, line 61 - line 68 ----	1
	----- -/--	

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 95 35340 A (FRAUNHOFER GES FORSCHUNG ;WEIGEL PETER (DE); FINK HANS PETER (DE);) 28 December 1995 (1995-12-28) examples 1,3 ----	1
A	US 3 767 756 A (BLADES H) 23 October 1973 (1973-10-23) figure 2 ----	2
A	US 1 654 253 A (W.F. HENDERSON) 27 December 1927 (1927-12-27) figure 1 ----	2
A	EP 0 483 562 A (LINDE AG) 6 May 1992 (1992-05-06) claims 1,8; figure 1 ----	2
A	EP 0 662 283 A (VISKASE CORP) 12 July 1995 (1995-07-12) claim 1 ----	2,3
A	WO 96 20301 A (FRAUNHOFER GES FORSCHUNG ;AKZO NOBEL FASER AG (DE); WEIGEL PETER () 4 July 1996 (1996-07-04) claim 1 ----	4
A	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 04, 30 April 1996 (1996-04-30) & JP 07 330945 A (ASAHI CHEM IND CO LTD), 19 December 1995 (1995-12-19) abstract ----	4
A	WO 97 37392 A (COURTAULDS FIBRES HOLDINGS LTD ;ASKEW GREGORY JAMES (GB); LAW STEP) 9 October 1997 (1997-10-09) claims 1,12-15; figure 1 ----	4
A	DE 195 15 137 A (THUERINGISCHES INST FUER TEXTI) 31 October 1996 (1996-10-31) claim 1 ----	5
A	WO 98 42492 A (SCHLOSSNIKL CHRISTIAN ;GSPALTL PETER (AT); KOFLER ALOIS (AT); CHEM) 1 October 1998 (1998-10-01) claims 1-12 ----	3-6
P,A	EP 0 899 076 A (KALLE NALO GMBH & CO KG) 3 March 1999 (1999-03-03) the whole document -----	3-6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03439

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4416698 A	22-11-1983	US 4246221 A	20-01-1981
		US 4144080 A	13-03-1979
		AT 387792 B	10-03-1989
		AT 268679 A	15-08-1988
		AU 4593779 A	04-09-1980
		BE 875323 A	04-10-1979
		CA 1141913 A	01-03-1983
		DD 142898 A	16-07-1980
		DE 2913589 A	11-09-1980
		ES 479450 A	16-10-1979
		FR 2450293 A	26-09-1980
		GB 2043525 A,B	08-10-1980
		IN 154748 A	15-12-1984
		IN 154757 A	15-12-1984
		IT 1115165 B	03-02-1986
		JP 1308043 C	13-03-1986
		JP 55118928 A	12-09-1980
		JP 60028848 B	06-07-1985
		NL 7902782 A	04-09-1980
		NO 791041 A	03-09-1980
		SE 444191 B	24-03-1986
		SE 7902733 A	03-09-1980
		TR 20668 A	21-04-1982
		AR 225004 A	15-02-1982
		AT 364900 B	25-11-1981
		AT 543978 A	15-04-1981
		AU 3814778 A	24-01-1980
		BE 868737 A	03-11-1978
		BR 7804794 A	03-04-1979
		CA 1116808 A	26-01-1982
		DD 140356 A	27-02-1980
		DE 2830685 A	15-02-1979
		DK 330978 A	27-01-1979
		ES 472037 A	01-02-1979
		FI 782170 A,B,	27-01-1979
		FR 2398774 A	23-02-1979
		GB 2001320 A,B	31-01-1979
		GR 64549 A	12-04-1980
		IN 147905 A	09-08-1980
		IT 1096905 B	26-08-1985
		JP 1048126 C	28-05-1981
		JP 54024963 A	24-02-1979
		JP 55041693 B	25-10-1980
		LU 79932 A	07-12-1978
		NL 7807421 A	30-01-1979
		NO 782556 A,B,	29-01-1979
		SE 445926 B	28-07-1986
		SE 7808039 A	27-01-1979
		TR 20127 A	01-09-1980
		ZA 7803707 A	25-07-1979
US 4196282 A	01-04-1980	US 4145532 A	20-03-1979
		AT 376986 B	25-01-1985
		AT 843478 A	15-06-1984
		AU 4181078 A	31-05-1979
		CA 1111206 A	27-10-1981
		DE 2848471 A	07-06-1979
		DK 525678 A	26-05-1979

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03439

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4196282	A		ES 476575 A	16-12-1979
			FI 783597 A,B,	26-05-1979
			FR 2423559 A	16-11-1979
			GB 2010279 A,B	27-06-1979
			IN 150398 A	25-09-1982
			IT 1101441 B	28-09-1985
			JP 1123841 C	30-11-1982
			JP 54099148 A	04-08-1979
			JP 57011566 B	05-03-1982
			LU 80571 A	16-05-1979
			NL 7811571 A	29-05-1979
			NO 783963 A	28-05-1979
			RO 77343 A	17-08-1981
			SE 443793 B	10-03-1986
			SE 7812131 A	26-05-1979
			TR 20125 A	19-09-1980
			US 4256613 A	17-03-1981
			US 4284545 A	18-08-1981
			BE 871895 A	01-03-1979
			ES 475378 A	01-12-1979
			JP 57085823 A	28-05-1982
			ZA 7805952 A	26-09-1979
EP 0822201	A	04-02-1998	JP 10045803 A	17-02-1998
			CN 1176253 A	18-03-1998
			US 5977347 A	02-11-1999
			US 5856468 A	05-01-1999
EP 0807460	A	19-11-1997	JP 10052630 A	24-02-1998
			US 6019925 A	01-02-2000
EP 0042517	A	30-12-1981	DE 3021943 A	21-01-1982
			AT 7206 T	15-05-1984
			AU 7147981 A	17-12-1981
			BR 8103677 A	02-03-1982
			CA 1171615 A	31-07-1984
			DD 159527 A	16-03-1983
			DK 254081 A	13-12-1981
			ES 502962 D	01-04-1982
			ES 8203629 A	16-07-1982
			FI 811840 A	13-12-1981
			GR 74574 A	29-06-1984
			JP 1771019 C	30-06-1993
			JP 4060692 B	28-09-1992
			JP 57024606 A	09-02-1982
			NO 811958 A	22-03-1982
			PT 73167 A,B	01-07-1981
			ZA 8103985 A	30-06-1982
US 3853448	A	10-12-1974	JP 48040855 A	15-06-1973
			DE 2244250 A	29-03-1973
			FR 2157796 A	08-06-1973
			IT 969444 B	30-03-1974
US 3950467	A	13-04-1976	JP 882949 C	30-09-1977
			JP 49111967 A	24-10-1974
			JP 52009224 B	15-03-1977
			DE 2409105 A	05-09-1974

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03439

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3950467	A		FR 2218986 A GB 1410573 A IT 1003583 B	20-09-1974 22-10-1975 10-06-1976
US 3280234	A	18-10-1966	BE 620293 A FR 1332817 A NL 280994 A US 3423400 A	16-12-1963 21-01-1969
DD 218104	A	30-01-1985	NONE	
US 3447939	A	03-06-1969	BE 703203 A BE 703240 A DE 1694047 A DE 1694048 A FR 1546629 A FR 1556993 A GB 1144048 A GB 1144759 A US 3508941 A	15-01-1968 15-01-1968 30-10-1969 05-02-1970 14-02-1969 28-04-1970
JP 01009715	A	13-01-1989	JP 1922560 C JP 6045168 B	07-04-1995 15-06-1994
JP 02049005	A	19-02-1990	JP 2745552 B	28-04-1998
EP 0528257	A	24-02-1993	GB 2258656 A AT 128404 T CA 2075779 A DE 69205102 D DE 69205102 T JP 5208417 A MX 9204732 A RU 2068291 C US 5351596 A ZA 9205825 A	17-02-1993 15-10-1995 16-02-1993 02-11-1995 18-04-1996 20-08-1993 01-07-1993 27-10-1996 04-10-1994 18-03-1993
EP 0375405	A	27-06-1990	JP 2165911 A JP 2625184 B JP 2165912 A JP 2625185 B JP 2165915 A JP 2625186 B JP 2165913 A JP 2625187 B JP 2165914 A AT 134558 T CA 2005995 C CA 2005995 A DE 68925804 D DE 68925804 T ES 2086321 T HK 194096 A KR 9210136 B SG 42317 A US 5034177 A US 5286187 A	26-06-1990 02-07-1997 26-06-1990 02-07-1997 26-06-1990 02-07-1997 26-06-1990 02-07-1997 26-06-1990 15-03-1996 22-03-1994 20-06-1990 04-04-1996 06-02-1997 01-07-1996 01-11-1996 16-11-1992 15-08-1997 23-07-1991 15-02-1994

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03439

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4144080	A	13-03-1979	AR 225004 A	15-02-1982
			AT 364900 B	25-11-1981
			AT 543978 A	15-04-1981
			AU 3814778 A	24-01-1980
			BE 868737 A	03-11-1978
			BR 7804794 A	03-04-1979
			CA 1116808 A	26-01-1982
			DD 140356 A	27-02-1980
			DE 2830685 A	15-02-1979
			DK 330978 A	27-01-1979
			ES 472037 A	01-02-1979
			FI 782170 A,B,	27-01-1979
			FR 2398774 A	23-02-1979
			GB 2001320 A,B	31-01-1979
			GR 64549 A	12-04-1980
			IN 147905 A	09-08-1980
			IT 1096905 B	26-08-1985
			JP 1048126 C	28-05-1981
			JP 54024963 A	24-02-1979
			JP 55041693 B	25-10-1980
			LU 79932 A	07-12-1978
			NL 7807421 A	30-01-1979
			NO 782556 A,B,	29-01-1979
			SE 445926 B	28-07-1986
			SE 7808039 A	27-01-1979
			TR 20127 A	01-09-1980
			US 4416698 A	22-11-1983
			ZA 7803707 A	25-07-1979
DE 4219658	A	23-12-1993	AT 173770 T	15-12-1998
			DE 4308524 C	22-09-1994
			EP 0574870 A	22-12-1993
			US 5417909 A	23-05-1995
WO 9535340	A	28-12-1995	DE 4421482 A	21-12-1995
			EP 0766709 A	09-04-1997
			JP 10501570 T	10-02-1998
US 3767756	A	23-10-1973	NONE	
US 1654253	A	27-12-1927	NONE	
EP 0483562	A	06-05-1992	DE 4034234 A	30-04-1992
EP 0662283	A	12-07-1995	US 5451364 A	19-09-1995
			US 5658524 A	19-08-1997
WO 9620301	A	04-07-1996	DE 4446491 C	27-06-1996
			AU 4326996 A	19-07-1996
			EP 0799332 A	08-10-1997
			US 5993710 A	30-11-1999
JP 07330945	A	19-12-1995	NONE	
WO 9737392	A	09-10-1997	AU 2039197 A	22-10-1997
			BR 9708490 A	03-08-1999
			CN 1215505 A	28-04-1999
			EP 0891640 A	20-01-1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03439

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
DE 19515137	A	31-10-1996	WO	9634037 A	31-10-1996
WO 9842492	A	01-10-1998	AT	404595 B	28-12-1998
			AT	49597 A	15-05-1998
			AU	6385098 A	20-10-1998
			CA	2255638 A	01-10-1998
			CN	1219148 T	09-06-1999
			EP	0904187 A	31-03-1999
			NO	985399 A	20-11-1998
EP 0899076	A	03-03-1999	DE	19737113 A	04-03-1999
			US	6033618 A	07-03-2000